

RAKE

where are the renders?



FEATURES:

- 90% of process water recycled
- High capacity flow rates
- Maximum flocculent efficiently
- Consistent underflow

AGGREGATES

RECYCLING

INDUSTRIAL SANDS





RAKE THICKENER

- High torque motor with torque measurement system for accurate desludging weither the sludge is destined for further processing or is simply being discharged to a pond.
- Heavy-duty full bridge design (built to last).
- Fully automated control system
- Skimmer option to remove floatable contaminants
- Available as highy mobile skid mounted version


Machine Model	MR-060	MR-080	MR-100	MR-120	MR-150
Height (M)	5.7	6.5	7.1	7.5	8.5
Diameter (M)	6	8	10	12	14
Solids Tonnage (MTPH)	10	16	25	35	45



LOW LEVEL RAKE THICKENER

- Fully automated control system
- Skimmer option to remove floatable contaminants
- Best suited to high flow applications
- Specially designed feed chamber to mix flocculants to gain optimum agglomeration

Machine Model	LLR-100	LLR-120	LLR-140	LLR-160	LLR-180	LLR-200	LLR-220
Height (M)	6.5	6.5	6.5	6.5	6.5	6.5	6.5
Diameter (M)	10	12	14	16	18	20	22
Solids Tonnage (MTPH)	25	35	45	52	60	75	90



2



DEDICATED TO WASHING, DEDICATED TO YOU



#LETUSCLARIFY

FARLOUGH SITE

32 Farlough Road, Dungannon, Co. Tyrone, Northern Ireland, BT71 4DT

Tel: +44(0) 28 8771 8500 Email: TWS.sales@terex.com

www.terexwashing.com (in)



