

Powerscreen® Trakpactor 320 – Mobile Impact Crusher

TRANSPORT DIMENSIONS

Length: 14.78m (48'6")
Height: 3.46m (11'4")
Width: 2.55m (8'4")
Weight (Est): 33,200kg (36.6 US Ton)

CRUSHER

- Twin apron
- 4 Bar rotor
- Hydraulic adjust

HOPPER

- Wear resistant hopper
- Folding sides with hydraulically locking pins

VIBRATING PAN FEEDER

- Spring mounted vibrating pan
- Twin shaft vibrator
- Variable speed control

OUTPUT POTENTIAL

Up to 320tph (352 US tph)



PRODUCT CONVEYOR

- Hydraulic raise/lower
- Hydraulically folding for transport
- Dust suppression

POWER UNIT

- Tier 3/Stage 3A: CAT C9 Acert 242kW (325hp)
- Tier 4i/Stage 3B: Scania DC9 83A 257kW (350hp)



www.powerscreen.com



USP's of Powerscreen® Trakpactor 320

Features

Key Features

1. Fully independent hydraulic pre-screen
2. Hydraulically folding extended side conveyor
3. Hopper extensions added to the hopper
4. New hopper design features hydraulic locking pins
5. Full length product conveyor option
6. Under-pan feeder option
7. Extended hydraulically folding product conveyor option

Benefits

What this means for the customer

1. Improves fines removal and reduces chamber wear costs
2. New feature provides additional stockpiles of 3.7m
3. Increases hopper capacity allowing more material to be handled
4. Increases speed of setup time and removed the need for manual wedges
5. Improves material handling for quarry applications
6. Improves material handling for recycled applications
7. Increases the stockpile height to 4m