



COBRA 260

HOPPER / FEEDER

2.3m³ (3yd³) Hopper capacity
 Two stage 'Tine' grizzly feeder as standard
 26mm (1") Nominal spacing

IMPACT CRUSHER

860mm (34") x 610mm (24") Crusher inlet
 830mm (33") Wide x 860mm (34") diameter rotor
 2 High / 2 Low configuration as standard
 Max OSS – 120mm (4.75") upper; 55mm (2.25") lower
 Min CSS – 40mm (1.5") upper; 20mm (0.75") lower
 Hydraulic adjust and hydraulic overload protection as standard
 Rotor speed: 700 – 930 rpm (32 – 40m/s tip speed)

OUTPUT POTENTIAL

Upto 250tph

POWERUNIT

Tier 3: CAT C7.1 186kW/250Hp
 Tier 4: 202kW / 275Hp CAT C7.1 engine
 Direct drive to crusher via clutch and V belts

CONVEYORS

900mm (36") Wide product conveyer
 Product conveyer discharge height: 3250mm (10'8")

GENERAL

Intuitive colour screen control panel

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	12.05m (39'6")	2.5m (8'2")	3.2m (10'6")

Weight (with Side Conveyer & Magnet) – 27000Kgs (59525lbs)